

查询"CS1214GF160"供应商

## SPECIFICATIONS

|                       |                              |
|-----------------------|------------------------------|
| Electrical Ratings    | 50mA @ 50VDC                 |
| Electrical Life       | 500,000 cycles typical       |
| Contact Resistance    | < 50 mΩ initial              |
| Actuation Force       | 160 +/- 50gF<br>260 +/- 50gF |
| Actuator Travel       | .25 +/- .1mm                 |
| Dielectric Strength   | 250Vrms min                  |
| Insulation Resistance | > 100MΩ min                  |
| Operating Temperature | -40°C to 85°C                |
| Storage Temperature   | -40°C to 85°C                |

## MATERIALS ←RoHS COMPLIANT


|           |                                |
|-----------|--------------------------------|
| Actuator  | Brass                          |
| Housing   | 4/6 Nylon                      |
| Cover     | Stainless Steel                |
| Contacts  | Stainless Steel, Silver Plated |
| Terminals | Brass, Silver Plated           |

## ORDERING INFORMATION


|                   |                                 |          |             |
|-------------------|---------------------------------|----------|-------------|
| <b>1. Series:</b> | <b>CS1214</b>                   | <b>J</b> | <b>F160</b> |
|                   | CS1214                          |          |             |
|                   | CS1214E (Earth Ground terminal) |          |             |

## DIMENSIONS

## SCHEMATIC & PC LAYOUTS



**CS1214EG**



**CS1214EJ**

