



Low Capacitance ESD Protection Diodes for High-Speed Data Interfaces



MARKING (example only)



Bar = cathode marking

YYY = type code (see table below)

XX = date code

FEATURES

- IEC 61000-4-5 (lightning) see I_{PPM} below
- ESD-protection acc. IEC 61000-4-2
± 8 kV contact discharge
± 15 kV air discharge
- Small package for use in portable electronics
- Space saving SOT-23 package
- High temperature soldering guaranteed:
260 °C/10 s at terminals
- Low capacitance for high speed data lines, cellular handsets, USB port protection, LAN equipment, peripherals
- AEC-Q101 qualified
- e3 - Sn
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC



ORDERING INFORMATION

DEVICE NAME	ENVIRONMENTAL STATUS	ORDERING CODE	TAPED UNITS PER REEL (8 mm TAPE ON 7" REEL)	MINIMUM ORDER QUANTITY
GL05T	Standard	GL05T-GS08	3000	15 000
	Green	GL05T-V-G-08		
GL12T	Standard	GL12T-GS08	3000	15 000
	Green	GL12T-V-G-08		
GL15T	Standard	GL15T-GS08	3000	15 000
	Green	GL15T-V-G-08		
GL24T	Standard	GL05T-GS08	3000	15 000
	Green	GL05T-V-G-08		

PACKAGE DATA

DEVICE NAME	PACKAGE NAME	TYPE CODE	ENVIRONMENTAL STATUS	WEIGHT	MOLDING COMPOUND FLAMMABILITY RATING	MOISTURE SENSITIVITY LEVEL	SOLDERING CONDITIONS
GL05T	SOT-23	L05	Standard	8.8 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals
		L06	Green	8.1 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals
GL12T	SOT-23	L12	Standard	8.8 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals
		L13	Green	8.1 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals
GL15T	SOT-23	L15	Standard	8.8 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals
		L16	Green	8.1 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals
GL24T	SOT-23	L24	Standard	8.8 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals
		L25	Green	8.1 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals

** Please see document "Vishay Material Category Policy": www.vishay.com/doc?99902

ABSOLUTE MAXIMUM RATINGS GL05T

PARAMETER	TEST CONDITIONS	SYMBOL	VALUE	UNIT
Peak pulse current	8/20 μ s	I_{PPM}	17	A
Peak pulse power	8/20 μ s waveform	P_{PP}	300	W
ESD immunity	Contact discharge acc. IEC 61000-4-2; 10 pulses	V_{ESD}	± 8	kV
	Air discharge acc. IEC 61000-4-2; 10 pulses		± 15	kV
Operating temperature	Junction temperature	T_J	- 55 to + 125	°C
Storage temperature		T_{STG}	- 55 to + 150	°C

ABSOLUTE MAXIMUM RATINGS GL12T

PARAMETER	TEST CONDITIONS	SYMBOL	VALUE	UNIT
Peak pulse current	8/20 μ s	I_{PPM}	12	A
Peak pulse power	8/20 μ s waveform	P_{PP}	300	W
ESD immunity	Contact discharge acc. IEC 61000-4-2; 10 pulses	V_{ESD}	± 8	kV
	Air discharge acc. IEC 61000-4-2; 10 pulses		± 15	kV
Operating temperature	Junction temperature	T_J	- 55 to + 125	°C
Storage temperature		T_{STG}	- 55 to + 150	°C

ABSOLUTE MAXIMUM RATINGS GL15T

PARAMETER	TEST CONDITIONS	SYMBOL	VALUE	UNIT
Peak pulse current	8/20 μ s	I_{PPM}	10	A
Peak pulse power	8/20 μ s waveform	P_{PP}	300	W
ESD immunity	Contact discharge acc. IEC 61000-4-2; 10 pulses	V_{ESD}	± 8	kV
	Air discharge acc. IEC 61000-4-2; 10 pulses		± 15	kV
Operating temperature	Junction temperature	T_J	- 55 to + 125	°C
Storage temperature		T_{STG}	- 55 to + 150	°C

ABSOLUTE MAXIMUM RATINGS GL24T

PARAMETER	TEST CONDITIONS	SYMBOL	VALUE	UNIT
Peak pulse current	8/20 μ s	I_{PPM}	5	A
Peak pulse power	8/20 μ s waveform	P_{PP}	300	W
ESD immunity	Contact discharge acc. IEC 61000-4-2; 10 pulses	V_{ESD}	± 8	kV
	Air discharge acc. IEC 61000-4-2; 10 pulses		± 15	kV
Operating temperature	Junction temperature	T_J	- 55 to + 125	°C
Storage temperature		T_{STG}	- 55 to + 150	°C

ELECTRICAL CHARACTERISTICS GL05T

PARAMETER	TEST CONDITIONS/REMARKS	SYMBOL	MIN.	TYP.	MAX.	UNIT
Protection paths	Number of lines which can be protected	$N_{channel}$	-	-	-	lines
Reverse working voltage	at $I_R = 1 \mu A$	V_{RWM}	5	-	-	V
Reverse current	at $V_R = 5 V$	I_R	-	-	20	μA
Reverse breakdown voltage	at $I_R = 1 mA$	V_{BR}	6	-	-	V
Reverse clamping voltage	at $I_{PP} = 1 A$	V_C	-	-	9.8	V
	at $I_{PP} = 5 A$		-	-	11	V
Capacitance	at $V_R = 0 V$; $f = 1 MHz$	C_D	-	5	-	pF

ELECTRICAL CHARACTERISTICS GL12T

PARAMETER	TEST CONDITIONS/REMARKS	SYMBOL	MIN.	TYP.	MAX.	UNIT
Protection paths	Number of lines which can be protected	N_{channel}	-	-	-	lines
Reverse working voltage	at $I_R = 1 \mu\text{A}$	V_{RWM}	12	-	-	V
Reverse current	at $V_R = 5 \text{ V}$	I_R	-	-	1	μA
Reverse breakdown voltage	at $I_R = 1 \text{ mA}$	V_{BR}	13.3	-	-	V
Reverse clamping voltage	at $I_{\text{PP}} = 1 \text{ A}$	V_C	-	-	19	V
	at $I_{\text{PP}} = 5 \text{ A}$		-	-	24	V
Capacitance	at $V_R = 0 \text{ V}$; $f = 1 \text{ MHz}$	C_D	-	5	-	pF




ELECTRICAL CHARACTERISTICS GL15T

PARAMETER	TEST CONDITIONS/REMARKS	SYMBOL	MIN.	TYP.	MAX.	UNIT
Protection paths	Number of lines which can be protected	N_{channel}	-	-	-	lines
Reverse working voltage	at $I_R = 1 \mu\text{A}$	V_{RWM}	15	-	-	V
Reverse current	at $V_R = 5 \text{ V}$	I_R	-	-	1	μA
Reverse breakdown voltage	at $I_R = 1 \text{ mA}$	V_{BR}	16.7	-	-	V
Reverse clamping voltage	at $I_{\text{PP}} = 1 \text{ A}$	V_C	-	-	24	V
	at $I_{\text{PP}} = 5 \text{ A}$		-	-	33	V
Capacitance	at $V_R = 0 \text{ V}$; $f = 1 \text{ MHz}$	C_D	-	5	-	pF


ELECTRICAL CHARACTERISTICS GL24T

PARAMETER	TEST CONDITIONS/REMARKS	SYMBOL	MIN.	TYP.	MAX.	UNIT
Protection paths	Number of lines which can be protected	N_{channel}	-	-	-	lines
Reverse working voltage	at $I_R = 1 \mu\text{A}$	V_{RWM}	24	-	-	V
Reverse current	at $V_R = 5 \text{ V}$	I_R	-	-	1	μA
Reverse breakdown voltage	at $I_R = 1 \text{ mA}$	V_{BR}	26.7	-	-	V
Reverse clamping voltage	at $I_{\text{PP}} = 1 \text{ A}$	V_C	-	-	43	V
	at $I_{\text{PP}} = 5 \text{ A}$		-	-	55	V
Capacitance	at $V_R = 0 \text{ V}$; $f = 1 \text{ MHz}$	C_D	-	5	-	pF

PACKAGE DIMENSIONS in millimeters (inches): SOT-23



Foot print recommendation:



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.