


SAW Bandpass Filter 201142B

1. Features

- IF Bandpass Filter
- High Attenuation
- Single-Ended Operation
- DIP Package
- Maximum Storage Temperature Range : -40℃ ~ 85℃
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : D3825

Dimensions shown are nominal in millimeters

Base : Fe(SGCC), Au plating over Ni plated

Cap : Cu & Cr Alloy, Ni Plated

Termination : Kovar, Au Plated

Pin Configuration	
1	Input
6	Output
2, 5	Ground
Other	Case ground

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	201140B	
		Rev. Date	2004-04-19	
		Rev.	NI0007-CS04	1/5

SAW Bandpass Filter 201142B

3. Specifications

Fo = 70.0 MHz

Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	69.96	70.0	70.04
Insertion Loss	dB	-	23.5	25.0
1dB Bandwidth	MHz	-	9.8	-
3dB Bandwidth	MHz	10.0	10.1	-
40dB Bandwidth	MHz	-	11.13	11.25
Amplitude Ripple (Fo +/- 4.675 MHz)	dB	-	1.0	1.2
Group Delay Variation (Fo +/- 4.675 MHz)	Nsec	-	100	150
Absolute Delay	Usec	-	3.18	-
Ultimate Rejection	dB	50	55	-
Temperature Coefficient of Frequency	ppm/°C	-	-94	-

Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss


	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	201140B	
		Rev. Date	2004-04-19	
		Rev.	NI0007-CS04	2/5

SAW Bandpass Filter 201142B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



5. Marking Configuration

ITF¹⁾ 04A001²⁾

201142B³⁾

1) Manufacturer name

2) Lot Number



3) Part Number

 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	201140B	
		Rev. Date	2004-04-19	
		Rev.	NI0007-CS04	3/5

SAW Bandpass Filter 201142B



6. Typical Performance (at +25℃)



ITF Co., Ltd.
102-901, Bucheon Technopark 364,
Samjeong-Dong, Ojeong-Gu, Bucheon-City,
Gyeonggi-Do, Korea 421-809

Part No.

201140B

Rev. Date





2004-04-19

Rev.

NI0007-CS04

4/5

SAW Bandpass Filter 201142B



ITF Co., Ltd.
102-901, Bucheon Technopark 364,
Samjeong-Dong, Ojeong-Gu, Bucheon-City,
Gyeonggi-Do, Korea 421-809

Part No.

201140B

Rev. Date

2004-04-19

Rev.

NI0007-CS04

5/5