

# PHASE LOCKED OSCILLATOR

查询 611230 供应商

## MODEL 611230 (1600 MHz)



### Features

- Low Phase Noise: -133 dBc/Hz @ 100 kHz
- Low Spurious: -70 dBc Typical
- Internal Reference Design
- Environmental Screening Available

### Specifications

CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -20 °C to +70 °C
Frequency (MHz)	1600	1600
Output Power (dBm)	+10	+9
Variation Over Temperature (dBm)	±0.75	±1
Spurious (dBc)	-70	-60
Phase Noise (dB)	-86 dBc/Hz @ 100 Hz -115 dBc/Hz @ 1 kHz -123 dBc/Hz @ 10 kHz -121 dBc/Hz @ 30 kHz -133 dBc/Hz @ 100 kHz -144 dBc/Hz @ 1 MHz	
VSWR	1.5	2.0
Harmonics (dBc)	-25	-20
Lock Indicator	TTL (High=Locked)	TTL (Low=Unlocked)
Stability (ppm)	±1	±15
Storage Temperature	-55 °C	+125 °C
Supply Power DC	15	15
mA	150	160


### Description

Spectrum Microwave's Series 600 Phase Locked Oscillators use a High "Q" Coaxial Resonator in the resonant circuit. The circuit is lightly loaded to obtain the lowest phase noise possible.

The resonator is soldered to a printed circuit board and well grounded to minimize modulation sidebands during shock and vibration.

Buffer amplifiers are used to provide isolation from load VSWRs; Regulators filter noise on the DC input voltage.

External reference models are also available. A lock indicator circuit is provided to signal an out-of-lock condition.



Spectrum Microwave, Inc.

[www.SpectrumMicrowave.com](http://www.SpectrumMicrowave.com)

2707 Black Lake Place Phila, Pa. 19154  
PH: 215-464-4000 FAX: 215-464-4001

Rev.  
9/22/08



# PHASE LOCKED OSCILLATOR

[查询"611230"供应商](#)

## MODEL 611230 (1600 MHz)



### Outline Drawing

