

SS5817 THRU SS5819

查询"SS5817"供应商

SURFACE MOUNT SCHOTTKY BARRIER RECTIFIERS

Reverse Voltage - 20 to 40 V


Forward Current - 1 A

Features

- Plastic package has Underwriters Laboratory Classification 94V-0
- Metal silicon junction, majority carrier conduction
- For surface mount applications
- Guard ring for overvoltage protection
- Low power loss, high efficiency
- High current capability, Low forward voltage drop
- High surge capability

Mechanical Data

- **Case:** SMA (DO-214AC) molded plastic case
- **Terminals:** Solder plate, solderable per MIL-STD -750, method 2026
- **Polarity:** Color band denotes cathode end
- **Mounting Position:** Any



Maximum Ratings and Electrical Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, resistive or inductive load, for capacitive load, derate by 20%

Parameter	Symbols	SS5817	SS5818	SS5819	Units	
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	20	30	40	V	
Maximum RMS Voltage	V_{RMS}	14	21	28	V	
Maximum DC Blocking Voltage	V_{DC}	20	30	40	V	
Maximum Average Forward Rectified Current 0.375" (9.5 mm) Load Length at $T_L = 90^\circ\text{C}$	$I_{(AV)}$	1			A	
Peak Forward Surge Current 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC Method) at $T_L = 70^\circ\text{C}$	I_{FSM}	25			A	
Maximum Instantaneous Forward Voltage at 1 A	V_F	0.45	0.55	0.6	V	
Maximum Instantaneous Reverse Current at Rated DC Blocking Voltage	I_R	at $T_A = 25^\circ\text{C}$			0.5	mA
		at $T_A = 100^\circ\text{C}$			10	mA
Typical Junction Capacitance ¹⁾	C_J	110			pF	
Typical Thermal Resistance ²⁾	$R_{\theta JA}$	88			$^\circ\text{C}/\text{W}$	
Operating and Storage Temperature Range	T_J, T_S	- 65 to + 125			$^\circ\text{C}$	

¹⁾ Measured at 1 MHz and reverse voltage of 4 volts.


²⁾ Thermal Resistance (from Junction to Ambient) Vertical P.C.B Mounted, with 1.5 X 1.5" (38 X 38 mm) copper pads.

SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



Dated : 01/07/2008 J



SS5817 THRU SS5819

[查询"SS5817"供应商](#)

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE






FIG.6-TYPICAL TRANSIENT THERMAL IMPEDANCE



SEMTECH ELECTRONICS LTD.
 (Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002 Certificate No. 05103
 ISO 14001:2004 Certificate No. 7116
 ISO 9001:2000 Certificate No. 0506098

Dated : 01/07/2008 J