

Low Profile Bending Beam



FEATURES

- Rated capacities of 50 to 300 pounds
- Compact, low profile design
- *Sensorgage*™ sealed to IP65 standards
- *Cell Guard*™ Two Year Warranty
- Factory Mutual System Approved for Classes I, II, III; Divisions 1 and 2; Groups A through G. Also, Non-incendive ratings (No Barriers!).
- ISO 9001:2000 Certified manufacturing facilities

APPLICATIONS

- Bin and hopper weighing
- Belt conveyor scales
- Netweighing

RATED CAPACITIES




lbs

50, 75, 150, 300

FULL SCALE OUTPUT (FSO)

lbs

3.0 mV/V +15% / -10%



ISO
9001:2000

**Factory
Mutual
System**
Approved

IP
65


ACCURACY CLASS

	STANDARD
Max. No. Verification Intervals	--
Combined Error % FSO	≤ 0.03
Nonlinearity % FSO	≤ 0.03
Hysteresis % FSO	≤ 0.02
Creep Error % FSO	≤ 0.03 in 20 minutes
Temperature Effect on: • Zero % FSO/°F • Output % of Load/°F	≤ 0.0015 ≤ 0.0008

PERFORMANCE SPECIFICATIONS**Non-Repeatability % FSO:** ≤ 0.1 **Zero Balance % FSO:** ≤ 1.0 **Insulation Resistance:** >1000 Mohms at 50 VDC**Compensated Temp. Range:** 14° to 104°F [-10° to 40°C]**Operating Temp. Range:** 0° to 150°F [-18° to 65°C]**Storage Temp. Range:** -60° to 185°F [-50° to 85°C]**Input Resistance:** 380-450 Ohms**Output Resistance:** 349-355 Ohms**Recommended Excitation Voltage:** 10 Volts DC**Maximum Excitation Voltage:** 15 Volts DC**Safe Overload:** 150% of Rated Capacity**Ultimate Overload:** 300% of Rate Capacity**Sealing:** Meets IP65 Standards**Material:** Alloy Tool Steel**Finish:** Electroless Nickel Plated**CAPACITY**

	DEFLECTION	WEIGHT
50 - 75	0.012	3.0
150 - 300	0.018	3.0

Dimensions are in inches. Capacities are in pounds. Deflection is $\pm 10\%$. Specifications are subject to change. Certified drawings are available.

DIMENSIONAL OUTLINE DRAWING in inches**WIRING**

+ Excitation = Red; - Excitation = Black; + Output = Green; - Output = White

VISHAY TRANSDUCERS (VT) - SALES OFFICES**VT Americas**
Covina, CA

PH: +1-800-722-0820
FAX: +1-626-332-3418
vt.us@vishaymg.com

VT Canada
Toronto

PH: +1-416-251-2554
FAX: +1-416-251-2690
vt.can@vishaymg.com

VT UK
Basingstoke

PH: +44-125-646-2131
FAX: +44-125-647-1441
vt.uk@vishaymg.com

VT Sweden
Karlskoga

PH: +46-586-630-00
FAX: +46-586-630-99
vt.se@vishaymg.com

VT Germany
Heilbronn

PH: +49-7131-3901-260
FAX: +49-7131-3901-2666
vt.de@vishaymg.com

VT France
Chartres

PH: +33-2-37-33-31-20
FAX: +33-2-37-33-31-29
vt.fr@vishaymg.com

VT Spain
Madrid

PH: +34-91-7218890
FAX: +34-91-7219056
vt.es@vishaymg.com

VT Finland
Jorvas

PH: +358-(0)9-8194-220
FAX: +358-(0)9-8194-2211
vt.fi@vishaymg.com

VT Norway
Oslo

PH: +47-22-21-40-70
FAX: +47-22-21-92-10
vt.no@vishaymg.com

VT Israel
Netanya

PH: +972-9-863-8888
FAX: +972-9-863-8800
vt.il@vishaymg.com

VT China
Tianjin

PH: +86-22-2835-3503
FAX: +86-22-2835-7261
vt.prc@vishaymg.com

VT Taiwan*
Taipei

PH: +886-2-2696-0168
FAX: +886-2-2696-4965
vt.roc@vishaymg.com
*Asia except China