



Micro Commercial Components
21201 Itasca Street Chatsworth
CA 91311

Phone: (818) 701-4933

Fax: (818) 701-4939

FST12020 THRU FST120100

Features

- Metal of silicon rectifier, majority carrier conduction
- Guard ring for transient protection
- Low power loss high efficiency
- High surge capacity, High current capability

Maximum Ratings

- Operating Temperature: -65°C to +150°C
- Storage Temperature: -65°C to +150°C


MCC Part Number	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
FST12020	20V	14V	20V
FST12030	30V	21V	30V
FST12035	35V	24.5V	35V
FST12040	40V	28V	40V
FST12045	45V	31.5V	45V
FST12060	60V	42V	60V
FST12080	80V	56V	80V
FST120100	100V	70V	100V

Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	$I_{F(AV)}$	120 A	$T_A = 135^\circ\text{C}$
Peak Forward Surge Current	I_{FSM}	1200A	8.3ms, half sine
Maximum Instantaneous Forward Voltage	V_F		$I_{FM} = 60.0\text{A};$ $T_A = 25^\circ\text{C}$
FST12020-12045		.63 V	
FST12060		.75 V	
FST12080-120100		.84 V	
Maximum DC Reverse Current At Rated DC Blocking Voltage	I_R	2 mA	$T_A = 25^\circ\text{C}$
Typical Junction Capacitance	C_J	340pF	Measured at 1.0MHz, $V_R=4.0\text{V}$

120 Amp Schottky Barrier Rectifier 20 to 100 Volts


POWERMOD



DIMENSIONS					
DIM	INCH ES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	1.995	2.005	50.67	50.93	
B	.330	.325	7.62	8.26	
C	.495	.505	12.57	12.83	
D	.182	.192	4.62	4.88	
E	.990	1.010	25.12	26.65	
F	1.490	1.510	37.85	38.35	
G	1.500	1.525	38.10	38.70	
H	.120	.130	3.05	3.30	
J	-----	.400	-----	10.16	
K	.240	.260	6.10	6.60	
L	.490	.510	12.45	12.95	
M	.330	.350	8.38	6.90	
N	.175	.195	4.45	4.95	Ø
P	.035	.045	0.89	1.14	
Q	.445	.455	11.30	11.56	
R	.890	.910	22.61	23.11	


*Pulse Test: Pulse Width 300µsec, Duty Cycle 1%

Figure 1
Typical Forward Characteristics




Instantaneous Forward Current - Amperes versus
Instantaneous Forward Voltage - Volts

Figure 2
Forward Derating Curve




Average Forward Rectified Current - Amperes versus
Ambient Temperature - °C

Figure 3
Junction Capacitance




Junction Capacitance - pF versus
Reverse Voltage - Volts

Figure 4
Typical Reverse Characteristics



Instantaneous Reverse Leakage Current - MicroAmperes versus
Percent Of Rated Peak Reverse Voltage - Volts

Figure 5
Peak Forward Surge Current



Peak Forward Surge Current - Amperes versus
Number Of Cycles At 60Hz - Cycles