



T-58-07


ZNREF062

6.2V LOW POWER PRECISION REFERENCE SOURCE

The ZNREF062 is a monolithic integrated circuit providing a precise stable reference voltage of 6.17V at 500 μ A.

The circuit features a knee current of 150 μ A and operation over a wide range of temperatures and currents.

The ZNREF062 is available in a 3-pin metal can package with pin 2 offering a trim facility whereby the output voltage can be adjusted as shown in Fig.1. This facility is used when compensating for system errors or setting the reference output to a particular value. When the trim facility is not used, pin 2 should be left open circuit.



Pin connections (bottom view)

FEATURES

- Trimmable Output
- Excellent Temperature Stability
- Low Output Noise Figure
- Available in Two Temperature Ranges
- 1 and 2% Initial Voltage Tolerance Versions Available
- No External Stabilising Capacitor required in most cases
- Low Slope Resistance

ORDERING INFORMATION

Device	Tol. %	TC (ppm/ $^{\circ}$ C)	Temperature range
ZNREF062 AB	1	50	-55 $^{\circ}$ C to +110 $^{\circ}$ C
ZNREF062 C1	1	50	0 $^{\circ}$ C to +70 $^{\circ}$ C
ZNREF062 C2	2		

ABSOLUTE MAXIMUM RATINGS

Reference current	50mA*
Power dissipation	300mW
Operating temperature range	See ordering information
Storage temperature range	-55 $^{\circ}$ C to +175 $^{\circ}$ C
Soldering temperature for a maximum time of 10s	
Within $\frac{1}{16}$ in of the seating plane	300 $^{\circ}$ C
Within $\frac{1}{32}$ in of the seating plane	265 $^{\circ}$ C

* Below -25 $^{\circ}$ C this figure should be linearly derated to 20mA at +110 $^{\circ}$ C.




Fig.1 ZNREF062 application circuit

TEMPERATURE DEPENDENT ELECTRICAL CHARACTERISTICS

T-58-07

Parameter	Symbol	Initial voltage tolerance %	Grade AB -55 to 110°C		Grade C 0 to 70°C		Units
			Typ.	Max.	Typ.	Max.	
Output voltage change over relevant temperature range (See note (a))	ΔV_{REF}	1 & 2	26	40	6.5	22	mV
Output voltage temperature coefficient (See note (b))	TCV_{REF}	1 & 2	25	40	15	50	ppm/°C

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ\text{C}$ and Pin 2 o/c unless otherwise specified).

Parameter	Symbol	Min.	Typ.	Max.	Units	Comments
Output voltage 1% tolerance (AB C1) 2% tolerance (C2)	V_{REF}	6.11 6.05	6.17 6.17	6.23 6.29	V	$I_{REF} = 500\mu\text{A}$
Output voltage adjustment range	ΔV_{TRIM}	—	± 5	—	%	$R_T = 100k\Omega$
Change in TCV_{REF} with output adjustment	$TC\Delta V_{TRIM}$	—	0.8	—	ppm/°C/%	
Operating current range	I_{REF}	0.15	—	50	mA	See note (c)
Turn-on time Turn-off time	t_{on} t_{off}	— —	40 0.3	— —	μs	$R_L = 1k\Omega$
Output voltage noise (over the range 0.1 to 10Hz)	e_{np-p}	—	50	—	μV	Peak to peak measurement
Slope resistance	R_{REF}	—	2	3	Ω	$I_{REF} 0.5\text{mA}$ to 5mA, See note (d)

NOTES

- (a) **Output change with temperature (ΔV_{REF})**
The absolute maximum difference between the maximum output voltage and the minimum output voltage over the specified temperature range

$$\Delta V_{REF} = V_{max} - V_{min}$$

- (b) **Output temperature coefficient (TCV_{REF})**
The ratio of the output change with temperature to the specified temperature range expressed in ppm/°C.

$$TCV_{REF} = \frac{\Delta V_{REF} \times 10^6}{V_{REF} \times \Delta T} \text{ ppm/°C}$$

ΔT = Full temperature change.

- (c) **Operating current (I_{REF})**
Maximum operating current must be derated as indicated in maximum ratings.

- (d) **Slope resistance (R_{REF})**
The slope resistance is defined as $R_{REF} = \frac{\Delta V_{REF}}{\Delta I_{REF}}$ change in V_{REF} overspecified current range
 $\Delta I_{REF} = 5 - 0.5 = 4.5\text{mA}$ (typically)

- (e) **Line regulation**
The ratio of change in output voltage to the change in input voltage producing it.

$$\frac{R_{REF} \times 100}{V_{REF} \times R_s} \% / V \quad R_s = \text{Source resistance}$$

T-58-07




Fig.2 Dynamic Impedance (typical)




Fig.3 Typical temperature characteristics

T-58-07




Fig.4 I_{REF} derating for ZNREF062