

L.E.D. Indicators

Colours and Properties

Red, yellow and green LEDs are available in high intensity (standard) or extra super bright (Option).

LEDs are available for direct connection to 2.2 or 12Vdc, please specify.

For other voltages contact the factory.

Sealing to IP66 is available where shown.

The nylon base mouldings are polarity marked.

Chromed brass or black anodised aluminium bodies are available.

Items prefixed "A" are supplied as holders only without LEDs.

To create a catalogue number:

Refer to the 2 columns below (terminal and type).

Then state:


LED colour and body finish - black or chrome.



W
LED fitted

A
LED not fitted

W 1047 OO



3mm LED

6.3mm
6.3mm max.
T85°C

W
LED fitted

A
LED not fitted

W 1048 OO




5mm LED

8.0mm
5.5mm max.
T85°C

W
LED fitted

A
LED not fitted

W 1050 OO



5mm LED Focusing reflector

8.0mm
7.0mm max.
T85°C

W
LED fitted

A
LED not fitted

W 1048 OA Sealed to IP 66




5mm LED

8.0mm
5.5mm max.
T85°C

W
LED fitted

A
LED not fitted

W 1050 OA Sealed to IP 66



5mm LED Focusing reflector

8.0mm
7.0mm max.
T85°C

DIMENSIONS

