


- **Open-Loop Voltage Amplification**
... 3600 Typ
- **CMRR** ... 100 dB Typ
- **Designed to be Interchangeable with Fairchild μ A702**

description


The μ A702 is a high-gain, wideband operational amplifier having differential inputs and single-ended emitter-follower outputs. Provisions are incorporated within the circuit whereby external components may be used to compensate the amplifier for stable operation under various feedback or load conditions. Component matching, inherent in silicon monolithic circuit-fabrication techniques, produces an amplifier with low-drift and low-offset characteristics. The μ A702 is particularly useful for applications requiring transfer or generation of linear and nonlinear functions up to a frequency of 30 MHz.

The μ A702 is characterized for operation over the full military temperature range of -55°C to 125°C .


symbol



**JG DUAL-IN-LINE PACKAGE
(TOP VIEW)**




**U FLAT PACKAGE
(TOP VIEW)**



NC—No internal connection

schematic



Component values shown are nominal

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage V_{CC+} (see Note 1)	14 V
Supply voltage V_{CC-} (see Note 1)	-7 V
Differential input voltage (see Note 2)	± 5 V
Input voltage (either input, see Notes 1 and 3)	-6 V to 1.5 V
Peak output current ($t_W \leq 1$ s)	50 mA
Continuous total dissipation at (or below) 70°C free-air temperature (see Note 4)	300 mW
Operating free-air temperature range	-55°C to 125°C
Storage temperature range	-65°C to 150°C
Lead temperature 1,6 mm (1/16 inch) from case for 60 seconds	300°C

- NOTES: 1. All voltage values, unless otherwise noted, are with respect to the network ground terminal.
 2. Differential voltages are at the noninverting input terminal with respect to the inverting input terminal.
 3. The magnitude of the input voltage must never exceed the magnitude of the lesser of the two supply voltages.
 4. For operation above 70°C free-air temperature, refer to Dissipation Derating Curves, Section 2. In the JG packages, μ A702M chips are alloy-mounted.

TYPE μ A702M
GENERAL-PURPOSE OPERATIONAL AMPLIFIER

electrical characteristics at specified free-air temperature

PARAMETER	TEST CONDITIONS†		$V_{CC+} = 12\text{ V}$ $V_{CC-} = -6\text{ V}$			$V_{CC+} = 6\text{ V}$ $V_{CC-} = -3\text{ V}$			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO} Input offset voltage	$R_S \leq 2\text{ k}\Omega$	25°C	0.5		2	0.7		3	mV
		Full range			3			4	
α_{VIO} Average temperature coefficient of input offset voltage	$R_S = 50\ \Omega$	-55°C to 25°C	2		10	3		15	$\mu\text{V}/^\circ\text{C}$
		25°C to 125°C	2.5		10	3.5		15	
I_{IO} Input offset current		25°C	0.2		0.5	0.12		0.5	μA
		-55°C	0.4		1.5	0.3		1.5	
		125°C	0.08		0.5	0.05		0.5	
α_{IIO} Average temperature coefficient of input offset current		-55°C to 25°C	3		16	2		13	nA/°C
		25°C to 125°C	1		5	0.7		4	
I_{IB} Input bias current		25°C	2		5	1.2		3.5	μA
		-55°C	4.3		10	2.6		7.5	
V_{ICR} Common-mode input voltage range	Positive swing	25°C	0.5		1	0.5		1	V
	Negative swing		-4		-5	-1.5		-2	
V_{OM} Maximum peak output voltage swing	$R_L \geq 100\text{ k}\Omega$	25°C	± 5		± 5.3	± 2.5		± 2.7	V
		Full range	± 5			± 2.5			
	$R_L = 10\text{ k}\Omega$	25°C	± 3.5		± 4	± 1.5		± 2	
		Full range	± 3.5			± 1.5			
A_{VD} Large-signal differential voltage amplification	$R_L \geq 100\text{ k}\Omega$	$V_O = \pm 5\text{ V}$	25°C	2500	3600	6000			
		Full range	2000		7000				
	$V_O = \pm 2.5\text{ V}$	25°C				600	900	1500	
		Full range				500		1750	
r_i Input resistance		25°C	16		40	22		87	k Ω
		Full range	6			8			
r_o Output resistance	$V_O = 0$, See Note 5	25°C	200		500	300		700	Ω
CMRR Common-mode rejection ratio	$R_S \leq 2\text{ k}\Omega$	25°C	80		100	80		100	dB
		Full range	70			70			
k_{SVS} Supply voltage sensitivity ($\Delta V_{IO}/\Delta V_{CC}$)	$R_S \leq 2\text{ k}\Omega$	25°C	75			75			$\mu\text{V}/\text{V}$
		Full range			200			200	
I_{CC} Supply current	No load, No signal	25°C	5		6.7	2.1		3.3	mA
		-55°C	5		7.5	2.1		3.9	
		125°C	4.4		6.7	1.7		3.3	
P_D Total power dissipation	No load, No signal	25°C	90		120	19		30	mW
		-55°C	90		135	19		35	
		125°C	80		120	15		30	

†All characteristics are specified under open-loop operation. Full range is -55°C to 125°C.

NOTE 5: This typical value applies only at frequencies above a few hundred hertz because of the effects of drift and thermal feedback.



Operational Amplifiers

TYPE μ A702M
GENERAL-PURPOSE OPERATIONAL AMPLIFIER

operating characteristics $V_{CC+} = 12\text{ V}$, $V_{CC-} = -6\text{ V}$, $T_A = 25^\circ\text{C}$

PARAMETER	TEST FIGURE	TEST CONDITIONS	MIN	TYP	MAX	UNIT
t_r Rise time	1	$V_I = 10\text{ mV}$, $C_L = 0$		25	120	ns
	2	$V_I = 1\text{ mV}$		10	30	ns
Overshoot factor	1	$V_I = 10\text{ mV}$, $C_L = 100\text{ pF}$		10%	50%	
	2	$V_I = 1\text{ mV}$		20%	40%	
SR Slew rate	1	$V_I = 6\text{ V}$, $C_L = 100\text{ pF}$		1.7		$\text{V}/\mu\text{s}$
	2	$V_I = 100\text{ mV}$		11		

PARAMETER MEASUREMENT INFORMATION




FIGURE 1—UNITY-GAIN AMPLIFIER






FIGURE 2—GAIN-OF-100 AMPLIFIER

3





Operational Amplifiers

TYPE μ A702M
GENERAL-PURPOSE OPERATIONAL AMPLIFIER

TYPICAL CHARACTERISTICS



**LAG COMPENSATION CIRCUIT
 FOR FIGURES 3, 4, AND 5**



**LEAD-LAG COMPENSATION CIRCUIT
 FOR FIGURE 6**

3

Operational Amplifiers