


Central Semiconductor Corp.
 Central Semiconductor Corp.
 Central Semiconductor Corp.
 145 Adams Avenue
 Hauppauge, New York 11788



CMCL1300 THRU CMCL1304

CURRENT LIMITING DIODE

JEDEC DO-35 CASE

FEATURES

- LOW COST
- HIGH RELIABILITY
- SMALLER CASE SIZE THAN COMPETITION
- SPECIAL SELECTIONS AVAILABLE
- SUPERIOR LOT TO LOT CONSISTENCY
- SURFACE MOUNT DEVICES AVAILABLE

DESCRIPTION


The CENTRAL SEMICONDUCTOR CMCL1300 series types are silicon field effect current regulator diodes designed for applications requiring a constant current over a wide voltage range. These devices are manufactured in the cost effective DO-35 double plug case which provides many benefits to the user including space savings and improved thermal characteristics. Special selections of I_p (regulator current) are available for critical applications. This series is a direct replacement for MCL1300 through MCL1304 types, respectively. Lower cost units are available in the CCL0035 series.

MAXIMUM RATINGS ($T_L = 75^\circ C$)

	SYMBOL	UNIT
Peak Operating Voltage	POV	100 V
Power Dissipation	P_D	600 mW
Operating and Storage Junction Temperature	T_J, T_{STG}	-65 TO +200 $^\circ C$

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ C$)

TYPE NO.	REGULATOR CURRENT			DYNAMIC IMPEDANCE	KNEE IMPEDANCE	LIMITING VOLTAGE
	$I_p @ V_T = 25V$			$Z_T @ V_T = 25V$	$Z_K @ V_K = 6.0V$	$V_L @ I_L = 0.8 I_p \text{ MIN}$
	mA			M Ω	M Ω	V
	MIN	NOM	MAX	MIN	MIN	MAX
CMCL1300	0.20	0.50	0.80	4.00	0.50	1.0
CMCL1301	0.40	1.00	1.60	0.80	0.20	1.5
CMCL1302	1.40	2.00	2.60	0.40	0.10	2.0
CMCL1303	2.40	3.00	3.60	0.30	0.05	2.0
CMCL1304	3.40	4.00	4.60	0.25	0.025	2.5



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.060	.080	1.52	2.03
B	.140	.160	3.60	4.10
C	1.0	—	25.4	—
D	.018	.022	0.46	0.56

HERMETICALLY SEALED GLASS CASE WITH TINNED COPPER LEADS

145 Adams Avenue, Hauppauge, NY 11788 USA
 Tel: (631) 435-1110 • Fax: (631) 435-1824